

STEADICAM®

ARCHER²™

NEW

Archer²™, Archer² SP™ and Archer² SPV™ features

- High Definition compatible
- Open access camera mounting stage
- Integral tilt head, +/- 15°
- Optional, upgradeable motorized stage, one or two motors
- Two-section carbon fiber posts
- High precision, no tools gimbal
- Tango™ compatible
- Wide-range inertial control
- Precision adjustable battery
- Versatile monitor mount
- Choice of monitors
- Precision adjustable dual battery mounts, 12/24 volts
- Choice of battery types
- Lightweight

Additional Archer² SP™ features

- Non-foldable heavy-duty monitor and battery clamps
- Safety stops on monitor and battery rods

Archer² SPV™ features

- 4.3" LCD return monitor
- Additional stage power port
- Low profile nosebox (non-motorized)

- Affordable
- No-tools adjustments
- Standard LX vest
- G-50X arm: 29" (74cm) boom range
- 30 lb. (13.6kg) max payload capacity



The Tiffen Company
90 Oser Avenue, Hauppauge, NY 11788
1-800-645-2522 • 631-273-2500 • tiffen.com

©2013 The Tiffen Company. All rights reserved. Steadicam is a registered trademark of The Tiffen Company. Other companies and brand names are trademarks or registered trademarks of their respective companies. Patent pending. Specifications subject to change without notice.